



WINDOW GRAPHICS

CV610C/TC

6.0 mil. **Hi-Stat®** White Static Cling Vinyl
On a 10 pt. Board

Catalina Graphic Films' Mojave Digital Media for Window Graphics are ideal for with Eco-Solvent, Solvent, UV-Based, and Latex inkjet printers. These films are also available for Screen Printing, and can be top-coated for improved ink adhesion for printing methods such as Offset, Litho, Flexographic and UV printing.

RECOMMENDED APPLICATIONS
• Window
• Indoor
• Outdoor

OVERVIEW	
Face Film	6.0 ± 0.2 mils gloss clear TC flex vinyl
Adhesive	None
Liner	10 pt. Board
Gloss Level	High Gloss
Outdoor Durability	Up to 2 Years (interior of window glass)

SPECIFICATIONS	
Application	This product is a self clinging film, which requires no adhesive, applies quickly to most smooth polished surfaces and is easily removed. Some of the many uses include window advertising, POP window decals, price stickers, automotive window decals and reusable seasonal decals.
Total Product Thickness	15.0 ± 1.0 mils
Surface Tension	32 dynes minimum
Minimum Application Temperature	+40° F
Service Temperature Range	-10° F To +150° F.
Adhesion	Excellent (non top-coated side of the vinyl will adhere to glass and other highly polished surfaces. It is recommended not to apply the top-coated or printed side to glass as the ink may transfer to the glass upon removal of the film)
Durability	Two years (interior of window glass)
Chemical Resistance	Excellent (commercial window cleaners)
Shelf Life	Six months when stored at 70° F and 50% relative humidity.
Material Reuse	Printed decals can be reused if properly handled
Available Colors	White & Clear

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

**To order or request product samples,
contact your local authorized dealer**



Distributed by:



For more information visit
www.piedmontplastics.com