

UV HEAT REJECTION WINDOW FILM SR

(UHR80SR)

Details

- Heat & UV rejection clera film for décor at Sunlight window
- World class polyester film with excellent clarity and dimensional stability
- Permanent adhesive without residue behind.
- Scratch resistant top coating for only UV curable printer

* Installation Guideline

Handle with gloves to avoid marks during printing. Not suitable for uneven surfaces.

Indoor applications (Reverse Printing)

Wet mount recommended for larger applications.

Clean the mounting object before applying this film

Specifications

Length (ft)	100	Width (inch)	60"
Weight (gsm)	125	Coating	Resin
Caliper (mil)	3.8	Base Material	PET
Inner Core (inch)	3" Plastic core	Printer	UV
Surface	Clear	Adhesion at 180°, gf/inch	300 ≤

KEY FEATURES

- Heat Rejection 65% (IR Cut 86%)
- UV Rejection 99%
- Optically Clear PET film (VLT 75%)
- Permanent adhesive
- Scratch resistant version

Application

- Indoor window advertisements, Architectural window decorations,

General Information

- Printing Temp : Temperature 15 ~ 30°C (59 ~ 86 °F) / Humidity 30 ~ 60%
- Lamination : Optional
- Storage : Recommended to store in closed original packing in a cool 10 ~ 30°C (50 ~ 77 °F) and dry environment.
(Humidity 35 ~ 65% RH)
- Shelf Life : One year, stored in original packing at recommended temperature
(Coating warranty guaranteed for 6 months from date of purchase)

How to buy :

- Please call 1-470-359-2111 to place an order or visit www.naturamedia.us for additional information.
- **ICC Profiles are available** by calling the above number.

*Information provided here is subject to our test criteria and subject to change without prior notice. No media warranty is implied.
All material should be tested by purchaser to determine final suitability. Printer and ink change may affect results.*

Distributed by:

 **Piedmont Plastics®**
where solutions take shape

For more information visit
www.piedmontplastics.com

Natura
MAKE A DIFFERENCE