

# Royalite® R61

## Low-smoke sheet

### Product Description

Royalite® R61 is a low-smoke, PVC/acrylic sheet that has an excellent balance of physical and mechanical properties while carrying bus and rail smoke ratings.

### Technical Properties

Property	Test Method	Value*
Specific Gravity (color dependent)	ASTM D-792	1.35-1.40
Izod Impact (Notched) 72°F	ASTM D-256	3.0 ft-lbs/in
Tensile Strength	ASTM D-638	5,900 psi
Flexural Strength	ASTM D-790	9,700 psi
Flexural Modulus	ASTM D-790	330,000 psi
Rockwell Hardness (R Scale)	ASTM D-785	103
Heat Deflection Temperature (@264 psi - annealed)	ASTM D-648	185°F
Coefficient of Linear Thermal Expansion	ASTM D-696	4.6 - 5.5 x10 <sup>-5</sup> in/in/°F
Bus and Rail Smoke Rating	UMTA/DOT/FRA	Passes
Motor Vehicle Safety Standard	FMVSS 302	Passes

\*All values based on 0.125" unless otherwise stated

For additional information, please contact Spartech at 800-677-4338 (800-67-SHEET), e-mail [info@spartech.com](mailto:info@spartech.com) or visit our website at [www.spartech.com](http://www.spartech.com)

Customers are responsible for determining whether products and information are appropriate for their use, including the evaluation of all applicable laws. Spartech LLC assumes no liability for the accuracy or completeness of information contained herein, and such information is subject to change without notice. All products supplied are subject to the standard terms and conditions of sale of Spartech LLC. **NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, IS MADE BY THIS TECHNICAL DATA SHEET. ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.**

Distributed by:

 **Piedmont Plastics®**  
[www.piedmontplastics.com](http://www.piedmontplastics.com)