

FLOORAPPEAL

NEW

INFINITY

MEDIA COMPANY

5350 East Avenue • Countryside, IL 60525

JUST PRINT, CUT, AND INSTALL!

**FloorAppeal can be applied to:
Indoor and Outdoor Surfaces**

Choose from 3 versions of FloorAppeal:

Low-Tac, High-Tac or High-Tac EX

Available in 30" & 54" wide rolls by 50' or 100'

LOW-TAC

Fantastic for all smooth indoor surfaces like metal, plastic laminates, wood, linoleum, tile & carpeting.

HIGH-TAC

Great for smooth outdoor surfaces like, concrete, paving stone, certain types of brick, untreated natural stone & plush/shag carpeting.

HIGH-TAC EX Most suitable for outdoor surfaces like aging concrete, asphalt & brick.

- Revolutionary scratch resistant fabric floor material with no need for lamination!
- Great for short term floor applications.
(We recommend Low-Tac for smooth indoor surfaces and High-Tac for rough outdoor surfaces)
- Printable with solvent, latex & UV printers
- Extremely durable and will not tear
- Bright white point washable surface
- Full Bleed Printing (no need to leave a white border)
- Easy Kiss-Cut or Contour Cut
- Safety Tested Anti-Slip (ASTM D-2047)
- Fire Rated (ASTM E-84)
- **Scratch Resistant • No Lamination Required • Leaves No Residue**



Distributed by:



Piedmont Plastics®
where solutions take shape

For more information visit
www.piedmontplastics.com

Versions, Sizes & Installation Suggestions

Choose from 3 versions of FloorAppeal:

Low-Tac, High-Tac or High-Tac EX

LOW-TAC optimally designed for all smooth indoor surfaces such as wooden platforms, metal, plastic laminate, linoleum, tile & carpeting.
use with: Solvent, UV & Latex inks.

Available Roll Sizes: 30", 54" x 50' and 30", 54" x 100'

HIGH-TAC most suitable for outdoor surfaces like, paving stone, concrete, cement, certain types of brick, untreated natural stone & plush/shag carpeting.
use with: Solvent, UV & Latex inks.

Available Roll Sizes: 30", 54" x 50' and 30", 54" x 100'

HIGH-TAC EX Most suitable for outdoor surfaces like aging concrete, asphalt & brick.
use with: Solvent, UV & Latex inks.

Available Roll Sizes: 30", 54" x 50' and 30", 54" x 100'

INSTALLATION SUGGESTIONS

- Surface must be absolutely dry and free from grease, oil stains, road salts, acids, sand & pebbles. (if surface isn't clean, the adhesive performance will be inhibited)
- Initially apply the material by hand. (using an applicator roller will help ensure the material conforms to whatever surface it is being applied to)
- Force all air bubbles out to ensure the material is completely adhered to the surface
- FloorAppeal works best when applied edge to edge with no overlapping

PRO TIP: tap edges of material with a rubber mallet or use a roller to help with sealing the graphic to the surface.



CLEANING

- When cleaning FloorAppeal products start in the middle and work your way out.
(cleaning from the edges toward the middle of the product may damage the adhesive properties of the product.)

NOTE: If power washing, use low pressure and keep at least 3½ feet away from the product

REMOVING

- Using a putty knife or razor, peel the material off at less than a 45° angle.

NOTE: FloorAppeal is easiest to remove under warm conditions

Disclaimer: There are some conditions which are beyond the manufacturer's control. The user is responsible for determining the products suitability including adhesion and removal characteristics. No legal responsibility can be claimed to the manufacturer or distributor.

Distributed by:



Piedmont Plastics®
where solutions take shape

For more information visit
www.piedmontplastics.com