

PRODUCT NAME:	ICGCP916		
PRODUCT CODE:			
PERFORMANCE TESTING:	Forced Entry: H.P. White Level I-TP-0500.02 ASTM 1915 Grade 4		
	Ballistic: .38 Special handgun, 3 shots in an 8" Circle, 158 grain lead, 20 feet. Spall with no penetration.		
CONSTRUCTION:	1/8" Chem-Tem or Heat Strengthened .050" Urethane 1/4" Polycarbonate .050" Urethane 1/8" Chem-Tem or Heat Strengthened		
THICKNESS:	.569" Nominal		
THICKNESS TOLERANCE:	.518" / .62"		
WEIGHT:	5.22 Lbs. / Square Foot		
MAXIMUM SIZE:	60"	x	96"
OPTIONS:	Tinted glass, transparent mirror, reflective glass, wire glass, Low E glass, insulated units. (The use of some options may alter product thickness)		
TECHNICAL DATA:	U-Value- .82 Solar Heat Gain Co-efficient- .71 Light Transmission- .77		
APPLICABLE STANDARDS:	ANSI Z97.1 ASTM C 1349 CPSC 16 CFR 1201 (Category I and II) ASTM C 1422 ASTM C 1036 ASTM C 1048		
SINGLE RESPONSIBILITY:	Global Security Glazing products are covered by our Single Responsibility® Program that ensures one firm has handled and is accountable for all phases of manufacturing.		
INSTALLATION:	All glass should be installed in accordance with the guidelines set forth in the current edition of the Glass Association of North America (GANA) Glazing and Sealant Manuals. Glazing systems should incorporate a weep system to allow moisture and water to escape the glazing channel.		
	Recommended Clearance: Face: 1/8" per side Edge: 1/4" Bite: 1"		