

panoRama iTacPlus™



Ultra-Removable Film With Repositionable
& Washable Adhesive Laminated With
panoRama iTP Protect™ Textured Laminate

APPLICATIONS

- Counter Mats, Elevator Graphics
- Vehicle Magnet Alternative For Vehicles With Aluminum Sides (Ford Trucks)

Distributed by



Piedmont Plastics®

CONTINENTAL
GRAFIX®

panoRama iTacPlus™

MATERIAL

Face Film	White Smooth Polyester (PET) And PVC
Backing	Silver - Adhesive Coated
Adhesive	Proprietary Washable Removable/Repositionable
Liner	Siliconized Paper Liner - 135g/m ²
Thickness	6.8mil (172 microns)
FR Certification	Not Tested
Slip Rating	None - Add <i>panoRama iTP Protect™</i> For Rating

DURABILITY

Interior	Up To 3 Years
Exterior	Up To 1 Year
Environment	Humidity & Solvent Resistance - Very Good
Shelf Life	12 Months
Storage Requirements	Store at +59°F to +68°F (+15°C to +20°C) with a Relative Humidity of 45% to 65%
Repositionable	Yes

APPLICATION/REMOVAL

Application Temp	+50°F to +86°F (+10°C to +30°C)
Service Temp	+0°F to +122°F (-17°C to +50°C)
Removability	Cleanly Removable With No Adhesive Residue, Adhesion May Increase On Certain Surfaces
Removal Temp	+20°F (-7°C) Or Greater
Exclusions	NOT To Be Applied On Fresh Paint, Polycarbonate, And Some PVC (No Exhaustive List Available)

Surface must be clean and dry. Prevent contact with solvent or ammonia based cleaners. For best results, clean surface with a mild detergent and water and dry thoroughly. Always clean and dry surface prior to application.



PRINTING METHODS

Digital - Solvent, Eco-Solvent, Latex & UV Inks; Screen Printing; Offset



MATERIAL SIZES

54" x 1312', 54" x 100', 54" x 50'



ADVANTAGES

- Great For Use As A Counter Mat
- Works As An Alternative To Using Magnetic Signs On Vehicles
- Washable/Reusable Adhesive Means You Can Reuse Graphics Again & Again Without Loss Of Adhesion

For additional product information, performance, and warranty guidelines please contact **Continental Grafix USA, Inc.** at 1.704.872.2216 or visit www.cgxusa.com.

Note: For critical substrates, always test prior to application.

Distributed by



Piedmont Plastics®

CONTINENTAL
GRAFIX®

panoRama iTP Protect™

MATERIAL

Face Film	Ultra Clear Textured Vinyl
Backing	Adhesive Backed
Adhesive	Permanent Clear Solvent Acrylic
Liner	Siliconized Paper Liner - 135g/m ²
Thickness	4.7mil (120 microns)
FR Certification	Not Tested
Slip Rating	ASTM D2047 & R10

DURABILITY

Interior	Up To 2 Years
Exterior	Up To 1 Year
Environment	Humidity & Solvent Resistance - Very Good
Shelf Life	12 Months
Storage Requirements	Store at +59°F to +68°F (+15°C to +20°C) with a Relative Humidity of 45% to 65%
Repositionable	NO

APPLICATION/REMOVAL

Application Temp	Min. Application Temp +50°F (+10°C)
Service Temp	+0°F to +122°F (-17°C to +50°C)
Lamination Method	Cold Lamination - In Some Cases A Small Amount Of Heat May Be Applied To Assist In Lamination
Removal Temp	+50°F (+10°C) Or Greater
Application Advice	Printed Material Should Be Fully Off Gassed Prior To Lamination - Surface Must Be Clean & Dry

Surface must be clean and dry. Prevent contact with solvent or ammonia based cleaners. For best results, clean surface with a mild detergent and water and dry thoroughly. Always clean and dry surface prior to application.



PRINTING METHODS
Not Applicable



MATERIAL SIZES
54" x 100', 54" x 50'



ADVANTAGES

- For Use With *panoRama iTacPlus™* As A Matched Component System
- Great Heat Resistance And Dimensional Stability For Excellent Durability
- Improves Finished Products Rigidity

For additional product information, performance, and warranty guidelines please contact **Continental Grafix USA, Inc.** at 1.704.872.2216 or visit www.cgxusa.com.

Note: For critical substrates, always test prior to application.

Distributed by



Piedmont Plastics®

CONTINENTAL
GRAFIX®