



Distributed by




Piedmont Plastics®

SLX** with Series 3210 Wrapped by Digital Precision



ARLON

PRINT MEDIA PRODUCTS



Your Partner of Choice.

At Arlon, we don't take this statement lightly. As a company that puts customers at the forefront, we like to think of ourselves as nimble—able to work quickly and respond to our customers needs.



Arlon, established in 1958 near Los Angeles, California, is a leading global manufacturer of pressure-sensitive adhesive vinyls for the sign and graphics industry. As one of the world's most experienced casting companies, Arlon has gained a worldwide reputation for quality and innovation.

Arlon is proudly ISO 9001:2015 certified.





WRAPITRIGHT.COM

WrapItRight.com gives you access to expert advice and tutorials from industry leaders and specialists!

- ▶ How-to video library featuring vehicle wraps, commercial signage, and digital printing techniques.
- ▶ Create custom playlists and watch videos later.
- ▶ Get updates on Trade Shows and Training Events.



Training & Certification

The Arlon Advanced Vehicle Wrap Training and Certification program was built by industry leading installers for installers wanting to take their wrap game to the next level. Learn in a hands-on environment to further develop your application skills and prove your expertise by taking the certification examination.

arlon.com/trainingandcertification

Arlon Technology



FLITE Technology®: Arlon's brand name for our lite contact system which allows graphics to easily reposition over a substrate until firm pressure is applied. FLITE Technology® guarantees the fastest install while ensuring long-term bond and clean removability.



X-Scape Technology®: Arlon's brand name for our air-egress technology which allows air to release through tiny channels in the adhesive backed vinyl used for fleet, vehicle and general signage applications. X-Scape Technology® allows installers to achieve a speedy installation while maintaining a high enough tack to ensure long-term bond.

arlon.com/technology



Being your partner of choice means more to us than you know. Arlon Graphics goal is to provide you with the highest quality products that perform how they should. Our products are supported by our comprehensive warranties to ensure your complete satisfaction.

arlon.com/warranties

Table of Contents

Cast Fleet & Vehicle Wraps	4
Calendered Fleet & Vehicle Wraps	6
Exterior Building & Wall Wraps	8
Commercial & Backlit Signage	10
Multi-Purpose	12
Interior Décor	14
Industrial	16
Promotional	18
Promotional Banner	20
Overlaminates	22
Specialty Overlaminates	24

Your Ideas in Motion

From start to finish, consistent print quality, ease of application, and versatility will keep your business moving no matter how many vehicles you're wrapping.



Wrapped in SLX*+ with Series 3210 by Poperzy

	DESCRIPTION	FACE FILM THICKNESS	ADHESIVE	RELEASE LINER	FINISH	APPLICATIONS
SLX*+	Premium Cast Film with Low Profile FLITE Technology®	2-Mil (50 Micron)	Clean Removing, Repositionable (Light Gray)	Lay-Flat Polycoated with Low Profile FLITE Technology®	Gloss	Vehicle Graphics (Full, Partial) Vehicle Decals / Fleet Graphics Stainless Steel
SLX* CAST WRAP	Premium Cast Film with Low Profile FLITE Technology®	2-Mil (50 Micron)	Clean Removing, Repositionable (Light Gray)	Lay-Flat Polycoated with Low Profile FLITE Technology®	Gloss	Vehicle Graphics (Full, Partial) Fleet Graphics
DPF 6100XLP	Premium Cast Film with Low Profile X-Scape Technology®	2-Mil (50 Micron)	Clean Removing, Repositionable (Light Gray)	Lay-Flat Polycoated with Low Profile X-Scape Technology®	Gloss	Vehicle Graphics (Full, Partial) Vehicle Decals / Fleet Graphics Multi-Purpose Commercial Wall Graphics (Interior, Exterior)
DPF 6000XRP	Premium Multi-Purpose Cast Film with X-Scape Technology®	2-Mil (50 Micron)	Clean Removing, Repositionable (Light Gray)	Lay-Flat Polycoated with X-Scape Technology®	Gloss	Vehicle Graphics (Full, Partial) Vehicle Decals / Fleet Graphics Multi-Purpose Commercial Wall Graphics (Interior, Exterior)
ILLUMINITE WRAP®	Fleet Grade * Reflective Film with Low Profile FLITE Technology®	5-Mil (125 Micron)	Permanent (Light Gray)	Lay-Flat Polycoated with Low Profile FLITE Technology®	Gloss	Vehicle Graphics (Full, Partial) Vehicle Decals / Fleet Graphics Fleet Markings
DPF 2400XLP	Fleet Grade * Reflective Film with Low Profile X-Scape Technology®	5-Mil (125 Micron)	Permanent (Light Gray)	Lay-Flat Polycoated with Low Profile X-Scape Technology®	Gloss	Vehicle Graphics (Full, Partial) Vehicle Decals / Fleet Graphics Fleet Markings
DPF 2400	Fleet Grade * Reflective Film	5-Mil (125 Micron)	Permanent (Clear)	Lay-Flat Polycoated	Gloss	Vehicle Graphics (Partial) / Vehicle Decals Fleet Graphics / Fleet Markings

* Fleet Grade exceeds engineering standards ✦ Only available in 54" width



Wrapped in IllumiNITE Wrap® with Series 3210 by Digital Precision



Wrapped in DPF 6100XLP with Series 3350 Overlaminate by I Sign It

RECOMMENDED SURFACES	DURABILITY (UNPRINTED)	ROLL WIDTHS	ROLL LENGTHS	COMPATIBLE OVERLAMINATE	INK COMPATIBILITY
Compound Curves / Deep Channels Concave Surfaces / Corrugated Panels Fleet Panels (Flat with Rivets) Stainless Steel	10 Years	30" / 48" 54" / 60"	25 Yards ♦ 50 Yards	Series 3200 / Series 3210 Series 3220 / Series 3270 Series 3310	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Compound Curves / Deep Channels Concave Surfaces / Corrugated Panels Fleet Panels (Flat with Rivets)	10 Years	30" / 48" 54" / 60"	50 Yards	Series 3200 / Series 3210 Series 3220 / Series 3270 Series 3310	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Compound Curves / Deep Channels Concave Surfaces / Corrugated Panels Fleet Panels (Flat with Rivets)	10 Years	30" / 48" 54" / 60"	25 Yards ♣ 50 Yards	Series 3200 / Series 3210 Series 3220 / Series 3270 Series 3310	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Compound Curves / Deep Channels Concave Surfaces / Corrugated Panels Fleet Panels (Flat with Rivets) / Smooth Walls	10 Years	30" / 48" 54" / 60"	25 Yards ♣ 50 Yards	Series 3200 / Series 3210 Series 3220 / Series 3270 Series 3310	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Smooth, Flat Panels / Compound Curves Moderate Channels / Soft Curves Concave Surfaces / Corrugated Panels Fleet Panels (Flat with Rivets)	7 Years	48"	10 Yards 25 Yards 50 Yards	Series 3210 Series 3220 Series 3200	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Smooth, Flat Panels / Compound Curves Moderate Channels / Soft Curves Fleet Panels (Flat with Rivets)	7 Years	48"	10 Yards 25 Yards 50 Yards	Series 3210 Series 3220 Series 3200	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Smooth, Flat Panels / Compound Curves Moderate Channels / Soft Curves Fleet Panels (Flat with Rivets)	7 Years	48"	10 Yards 25 Yards 50 Yards	Series 3210 Series 3220 Series 3200	Eco-Solvent / Solvent



WATCH THE VIDEO ▶

The Deep Channel Hack

Forcing vinyl into deep channels would cause over-stretching and in a short time the vinyl will shrink back and lift creating bubbles. This video shows you a quick way to avoid application failure in deep channels.

For more videos, visit wrapitright.com



THE POWER Of Heat!

Heat aids the removal process by reducing the likelihood of tearing and laminate separation.




Wrapped in DPF 45WF

Fuel your Brand

Providing you with end-to-end solutions that keep efficiency and price point in mind.

	DESCRIPTION	FACE FILM THICKNESS	ADHESIVE	RELEASE LINER	FINISH	APPLICATIONS
FUSION WRAP	High Performance Calendered Film with Low Profile FLITE Technology®	2.4-Mil (60 Micron)	Clean Removing, Repositionable (Light Gray)	Lay-Flat Polycoated with Low Profile FLITE Technology®	Gloss	Vehicle Graphics (Full, Partial) Vehicle Decals Fleet Graphics
DPF 4600GLX/MLX	High Performance Multi-Purpose Calendered Film with Low Profile X-Scape Technology®	3.2-Mil (80 Micron)	Clean Removing, Repositionable (Light Gray)	Lay-Flat Polycoated with Low Profile X-Scape Technology®	Gloss Matte	Vehicle Graphics (Partial) Vehicle Decals Fleet Graphics Window Graphics Multi-Purpose Commercial Wall Graphics (Interior) Floor Graphics (Interior) *
DPF 45WF	One-Way Vision Window Film 60/40 Perforated Pattern	6-Mil (150 Micron)	Clean Removing, Low Tack (Clear)	Lay-Flat Polycoated	Satin	Window Graphics

* Only when laminated with UL 410 Arlon overlaminates. Please refer to page 23 ✦ 7 year durability applies when paired with an Arlon cast overlaminate



Pitching a calendered wrap film can be the difference between bidding and winning a job. Knowing when and how to use calendered film is going to be key.

For more videos, visit wrapitright.com

▲ Optimal printing on HP Latex 360 ◆ Only available in Gloss

CHOOSING Calendered Film

Specifying a calendered film can give you an economic advantage in certain instances. Calendered films are ideal options for flat to simple curves, or short to medium term graphics.

Surfaces are not Equal

Transform hard-to-stick brick, concrete and stucco into larger than life graphics.
From the window to the walls, no surface is left untouched.



Wrapped in DPF 6700 by Daley Visual

	DESCRIPTION	FACE FILM THICKNESS	ADHESIVE	RELEASE LINER	FINISH	APPLICATIONS
DPF 6700	Premium Cast Wall Wrap Film	2-Mil (50 Micron)	Permanent (Clear)	Lay-Flat Polycoated	Gloss	Wall Graphics (Interior, Exterior)
DPF 8000™ ULTRA TACK	Industrial Grade Multi-Purpose Calendered Film for Hard-to-Stick Surfaces	3.5-Mil (90 Micron)	Permanent, Ultra Tack (Clear)	Lay-Flat Polycoated	Satin	Wall Graphics (Exterior) ABS Plastic Graphics Floor Graphics (Interior) *
DPF 8200X HIGH TACK	Industrial Grade Multi-Purpose Calendered Film with Low Profile X-Scape Technology®	3.5-Mil (90 Micron)	Permanent, High Tack (Clear)	Lay-Flat Polycoated with Low Profile X-Scape Technology®	Satin	Wall Graphics (Interior, Exterior) Low Surface Energy Substrates
DPF 8200 HIGH TACK	Industrial Grade Multi-Purpose Calendered Film for Exterior Wall and Low Surface Energy Substrates	3.5-Mil (90 Micron)	Permanent, High Tack (Clear)	Lay-Flat Polycoated	Satin	Wall Graphics (Interior, Exterior) Low Surface Energy Substrates Floor Graphics (Interior) *
DPF 47WF	One-Way Vision Window Film 70/30 Perforated Pattern	6-Mil (150 Micron)	Clean Removing, Low Tack (Clear)	Lay-Flat Polycoated	Satin	Window Graphics

* Only when laminated with UL 410 Arlon overlaminates. Please refer to page 23 ❖ See PIB for warranty exclusions ▲ 7 year durability applies when paired with an Arlon cast overlaminate



Wrapped in DPF 8200 High Tack



Wrapped in DPF 8000™ Ultra Track



WATCH THE VIDEO ▶

Tiling for Large Wall Graphics

Successful installations of large wall graphics are dependent upon preparation and good design practices. This video will show you how to prepare a graphic for installation.

For more videos, visit wrapitright.com

RECOMMENDED SURFACES	DURABILITY (UNPRINTED)	ROLL WIDTHS	ROLL LENGTHS	COMPATIBLE OVERLAMINATE	INK COMPATIBILITY
Brick, Concrete & Stucco Textured Surfaces & Substrates	7 Years ♣	30" / 48" 54" / 60"	50 Yards	Series 3200 / Series 3210 Series 3220 / Series 3310	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Brick, Concrete & Stucco Textured Surfaces & Substrates Smooth Walls ABS Plastics Smooth Floors	7 Years ♣ ▲	30" / 49" 54" / 60"	50 Yards	Series 3210 / Series 3220 Series 3310 / Series 3420 ProTec Series 3960	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Smooth and Textured Surfaces & Substrates Brick, Concrete & Stucco Low Surface Energy Substrates	7 Years ♣ ▲	54" / 60"	50 Yards	Series 3210 / Series 3220 Series 3310 / Series 3420 ProTec Series 3960	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Smooth and Textured Surfaces & Substrates Brick, Concrete & Stucco Low Surface Energy Substrates Smooth Floors / Low Pile Carpet	7 Years ♣ ▲	30" / 49" 54" / 60"	50 Yards	Series 3210 / Series 3220 Series 3310 / Series 3420 ProTec Series 3960	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Glass	1 Year	54" / 60"	164 Feet	Series 3200	Eco-Solvent / Solvent UV / Latex ♣

♣ Optimal printing on HP Latex 360



THE IMPORTANCE OF Outgassing

Before laminating your solvent printed graphic, always allow
24 hours of outgassing.

Make an Impact


Don't let your signage get lost in the crowd. Choosing a film with both flexibility and vibrant print quality will give you the visibility you need for your graphics to perform everyday.

	DESCRIPTION	FACE FILM THICKNESS	ADHESIVE	RELEASE LINER	FINISH	APPLICATIONS
DPF 4600GLX/MLX	High Performance Multi-Purpose Calendered Film with Low Profile X-Scape Technology®	3.2-Mil (80 Micron)	Repositionable (Light Gray)	Lay-Flat Polycoated with Low Profile X-Scape Technology®	Gloss Matte	Multi-Purpose Commercial Wall Graphics (Interior) Vehicle Graphics (Partial) Vehicle Decals Fleet Graphics Window Graphics Floor Graphics (Interior) *
DPF 4500GLX/MLX	Intermediate Calendered Film with Low Profile X-Scape Technology®	3-Mil (75 Micron)	Permanent (Light Gray)	Lay-Flat Polycoated with Low Profile X-Scape Technology®	Gloss Matte	Standard Signage (Permanent) Display Graphics
DPF 4500GX	Intermediate Calendered Film with Low Profile X-Scape Technology®	3-Mil (75 Micron)	Permanent (Clear)	Lay-Flat Polycoated with Low Profile X-Scape Technology®	Gloss	Standard Signage (Permanent) Display Graphics Window Graphics
DPF 4500GT/MT	Intermediate Calendered Film	3-Mil (75 Micron)	Permanent (Light Gray)	Lay-Flat Polycoated	Gloss Matte	Standard Signage (Permanent) Display Graphics
DPF 4500G WHITE/CLEAR	Intermediate Calendered Film	3-Mil (75 Micron)	Permanent (Clear)	Lay-Flat Polycoated	Gloss	Standard Signage (Permanent) Display Graphics Second Surface Signage ✦ Window Graphics ✦
DPF 6000RP CLEAR	Premium Clear Cast Film	2-Mil (50 Micron)	Permanent (Clear)	Lay-Flat Polycoated	Gloss	Backlit Signage Standard Signage (Permanent) Display Graphics Second Surface Signage Window Graphics Vehicle Graphics (Full, Partial) Fleet Graphics
DPF 6500	Premium Translucent Cast Film	2-Mil (50 Micron)	Permanent (Clear)	Lay-Flat Polycoated	Gloss	Backlit Signage Display Graphics



Wrapped in DPF 4600GLX

* Only when laminated with UL 410 Arlon overlaminates. Please refer to page 23 ✦ Use with DPF 4500G Clear ▲ 7 year durability applies when paired with an Arlon cast overlaminate




Wrapped in DPF 6000RP Clear

RECOMMENDED SURFACES	DURABILITY (UNPRINTED)	ROLL WIDTHS	ROLL LENGTHS	COMPATIBLE OVERLAMINATE	INK COMPATIBILITY
Common Sign Substrates / Glass Smooth Walls / Soft Curves Fleet Panels (Flat without Rivets) Smooth Floors	7 Years ▲	30" ♦ 54" / 60"	50 Yards	Series 3170 / Series 3210 Series 3220 / Series 3310 Series 3420	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Common Sign Substrates Glass	5 Years	30" / 48" ♦ 54" / 60"	50 Yards	Series 3170 / Series 3220 Series 3420	Eco-Solvent / Solvent UV / Latex
Common Sign Substrates Glass	5 Years	30" / 54" / 60"	50 Yards	Series 3170 / Series 3220 Series 3420	Eco-Solvent / Solvent UV / Latex
Common Sign Substrates Glass	5 Years	30" / 48" 54" / 60"	50 Yards	Series 3170 / Series 3220 Series 3420	Eco-Solvent / Solvent UV / Latex
Common Sign Substrates Glass	5 Years	30" / 48" 54" / 60"	50 Yards	DPF 4500G White: Series 3170 / Series 3220 Series 3420 DPF 4500G Clear: Series 3200	Eco-Solvent / Solvent UV / Latex ■
Glass / Common Sign Substrates Compound Curves / Deep Channels Concave Surfaces / Corrugated Panels Fleet Panels (Flat with Rivets)	7 Years	30" / 48" 54" / 60"	50 Yards	Series 3200	Eco-Solvent / Solvent UV / Latex
Glass / Sign Plexi Common Sign Substrates	7 Years	30" / 48" 54" / 60"	25 Yards ▼ 50 Yards	Series 3200 / Series 3210 Series 3220 / Series 3350	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks

♦ 48" width only available in Gloss ♦ Only available in Gloss ■ Not compatible with DPF 4500G Clear ▼ Only available in 54" width

WRAPITRIGHT®

INSTRUCTIONAL VIDEO LIBRARY



WATCH THE VIDEO ▶

The Hinge Method Made Easy

There's no better way to get a graphic application started than by making the perfect hinge using a double back-slitting knife. Watch this video and use the hinge method to make installation easier for you.

For more videos, visit wrapitright.com

PRO TIPS



HOW TO PREVENT Pre-adhesion

Using an application fluid for wet applications will help the graphic float onto the surface to prevent pre-adhesion.

Freedom of Application

This collection features our most versatile films allowing you to use them for multiple applications while maximizing profitability.



Wrapped in DPF 6100XLP

	DESCRIPTION	FACE FILM THICKNESS	ADHESIVE	RELEASE LINER	FINISH	APPLICATIONS
DPF 6100XLP	Premium Cast Film with Low Profile X-Scape Technology®	2-Mil (50 Micron)	Clean Removing, Repositionable (Light Gray)	Lay-Flat Polycoated with Low Profile X-Scape Technology®	Gloss	Vehicle Graphics (Full, Partial) Vehicle Decals Fleet Graphics Multi-Purpose Commercial Wall Graphics (Interior, Exterior)
DPF 6000XRP	Premium Multi-Purpose Cast Film with X-Scape Technology®	2-Mil (50 Micron)	Clean Removing, Repositionable (Light Gray)	Lay-Flat Polycoated with X-Scape Technology®	Gloss	Multi-Purpose Commercial Wall Graphics (Interior, Exterior) Vehicle Graphics (Full, Partial) Vehicle Decals / Fleet Graphics
DPF 6000RP WHITE	Premium Multi-Purpose Cast Film	2-Mil (50 Micron)	Clean Removing, Repositionable (Light Gray)	Lay-Flat Polycoated	Gloss	Multi-Purpose Commercial Wall Graphics (Interior, Exterior) Vehicle Graphics (Full, Partial) Vehicle Decals / Fleet Graphics
DPF 4600GLX/MLX	High Performance Multi-Purpose Calendered Film with Low Profile X-Scape Technology®	3.2-Mil (80 Micron)	Repositionable (Light Gray)	Lay-Flat Polycoated with Low Profile X-Scape Technology®	Gloss Matte	Multi-Purpose Commercial Wall Graphics (Interior) Vehicle Graphics (Partial) Vehicle Decals, Fleet Graphics Window Graphics Floor Graphics (Interior) *
DPF 8200X HIGH TACK	Industrial Grade Calendered Film with Low Profile X-Scape Technology®	3.5-Mil (90 Micron)	Permanent, High Tack (Clear)	Lay-Flat Polycoated with Low Profile X-Scape Technology®	Satin	Wall Graphics (Exterior, Interior) Low Surface Energy Substrates
DPF 8200 HIGH TACK	Industrial Grade Multi-Purpose Calendered Film for Exterior Wall and Low Surface Energy Substrates	3.5-Mil (90 Micron)	Permanent, High Tack (Clear)	Lay-Flat Polycoated	Satin	Wall Graphics (Exterior) Low Surface Energy Substrates Floor Graphics (Interior) *
DPF 510GTX/MTX	Promotional Calendered Permanent Film with Low Profile X-Scape Technology®	3.2-Mil (80 Micron)	Permanent (Light Grey)	Lay-Flat Polycoated with Low Profile X-Scape Technology®	Gloss Matte	Standard Signage (Permanent) Display Graphics Indoor Advertising Outdoor Advertising

* Only when laminated with UL 410 Arlon overlaminates. Please refer to page 23 ✦ 7 year durability applies when paired with an Arlon cast overlaminate



Wrapped in DPF 4600GLX



Wrapped in DPF 6000RP White by Graphics Unlimited

RECOMMENDED SURFACES	DURABILITY (UNPRINTED)	ROLL WIDTHS	ROLL LENGTHS	COMPATIBLE OVERLAMINATE	INK COMPATIBILITY
Smooth Walls / Compound Curves Deep Channels / Concave Surfaces Corrugated Panels Fleet Panels (Flat with Rivets)	10 Years	30" / 48" 54" / 60"	25 Yards ♦ 50 Yards	Series 3200 / Series 3210 Series 3220 / Series 3270 Series 3310	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Smooth Walls / Compound Curves Deep Channels / Concave Surfaces Corrugated Panels Fleet Panels (Flat with Rivets)	10 Years	30" / 48" 54" / 60"	25 Yards ♦ 50 Yards	Series 3200 / Series 3210 Series 3220 / Series 3270 Series 3310	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Smooth Walls / Compound Curves Deep Channels / Concave Surfaces Corrugated Panels Fleet Panels (Flat with Rivets)	10 Years	30" / 48" 54" / 60"	25 Yards ♦ 50 Yards	Series 3200 / Series 3210 Series 3220 / Series 3270 Series 3310	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Glass / Common Sign Substrates Smooth Walls / Soft Curves Fleet Panels (Flat without Rivets) Smooth Floors	7 Years ♣	30" ■ 54" / 60"	50 Yards	Series 3170 / Series 3210 Series 3220 / Series 3310 Series 3420	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Smooth and Textured Surfaces & Substrates Brick, Concrete & Stucco Low Surface Energy Substrates	7 Years ♣ ▲	54" / 60"	50 Yards	Series 3210 / Series 3220 Series 3310 / Series 3420 ProTec Series 3960	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Smooth and Textured Surfaces & Substrates Brick, Concrete & Stucco Low Surface Energy Substrates Smooth Floors / Low Pile Carpet	7 Years ♣ ▲	30" / 49" 54" / 60"	50 Yards	Series 3210 / Series 3220 Series 3310 / Series 3420 ProTec Series 3960	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Common Sign Substrates	3 Years	54" / 60"	50 Yards	Series 3510 Series 3420 Series 3220	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks

▲ See PIB for Warranty exclusions ♦ Only available in 54" width ■ Only available in Gloss

WRAPITRIGHT®

INSTRUCTIONAL VIDEO LIBRARY



WATCH THE VIDEO ▶

Uploading an Arlon Media Profile Into HP 300 Series Printers

Learn step-by-step instructions on how to properly upload Arlon Media Profiles into HP 300 RIP software.

For more videos, visit wrapitright.com

PRO  TIPS

FOR MAXIMUM Shelf Life

Problems like mottling, curling, and inconsistencies in release liners can be avoided by storing film at recommended temperatures.

Excess humidity and heat can greatly affect a film's shelf life—so keep your rolls both cool and dry!

Walls Reimagined

Transform ordinary walls into personalized art tailored to each individual customer.



Wrapped in DPF 4200 Canvas

	DESCRIPTION	FACE FILM THICKNESS	ADHESIVE	RELEASE LINER	FINISH	DURABILITY (UNPRINTED)
DPF 4200 MATTE / CANVAS	Permanent Calendered Wall Decoration Film	6-Mil (150 Micron)	Permanent (Clear)	Lay-Flat Polycoated	Matte Canvas	7 Years *
EVER ETCHED CAST	Printable Etched Glass Cast Film with FLITE Technology®	3-Mil (75 Micron)	Permanent (Clear)	Lay-Flat Polycoated with Low Profile FLITE Technology®	Etched Glass	15 Years *
EVER ETCHED CAL	Printable Etched Glass Calendered Film with FLITE Technology®	3-Mil (75 Micron)	Permanent (Clear)	Lay-Flat Polycoated with Low Profile FLITE Technology®	Etched Glass	7 Years *
DPF 5200	Printable Etched Glass Cast Film	2-Mil (50 Micron)	Permanent (Clear)	Lay-Flat Synthetic	Etched Glass Silver Etched Glass Sparkle Etched Glass	7 Years
DPF 6000RP WHITE	Premium Multi-Purpose Cast Film	2-Mil (50 Micron)	Clean Removing, Repositionable (Light Gray)	Lay-Flat Polycoated	Gloss	10 Years
DPF 4600GLX/MLX	High Performance Multi-Purpose Calendered Film with Low Profile X-Scape Technology®	3.2-Mil (80 Micron)	Repositionable (Light Gray)	Lay-Flat Polycoated with Low Profile X-Scape Technology®	Gloss Matte	7 Years ✦
DPF 4300	Intermediate Calendered Multi-Purpose Removable Film	3.4-Mil (86 Micron)	Removable (Clear)	Lay-Flat Polycoated	Matte	4 Years
DPF 206	Removable Coated Wall Fabric	6-Mil (150 Micron)	Removable (Clear)	Lay-Flat Polycoated	Matte	1 Year

* See PIB for warranty exclusions ✦ 7 year durability applies when paired with an Arlon cast overlamine ▲ Only available in 48" width ✦ Only available in 54" width



Wrapped in Ever Etched Cast



Wrapped in Ever Etched Cal

APPLICATIONS	RECOMMENDED SURFACES	ROLL WIDTHS	ROLL LENGTHS	COMPATIBLE OVERLAMINATE	INK COMPATIBILITY
Indoor Advertising Wall Graphics (Interior) Interior Décor	Common Sign Substrates Smooth Walls	54" / 60" ♦	25 Yards 50 Yards	N/A	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Window Graphics (Interior, Exterior *) Glass & Clear Substrates Partition Graphics	Glass Clear Substrates	54" / 60"	25 Yards 50 Yards	N/A	Eco-Solvent / Solvent UV / Latex
Window Graphics (Interior, Exterior *) Glass & Clear Substrates Partition Graphics	Glass Clear Substrates	54" / 60"	25 Yards 50 Yards	N/A	Eco-Solvent / Solvent UV / Latex
Window Graphics (Interior, Exterior *) Glass & Clear Substrates Partition Graphics	Glass Clear Substrates	24" / 30" 48" / 60"	10 Yards ▲ 50 Yards	N/A	Eco-Solvent / Solvent UV / Latex
Wall Graphics (Interior, Exterior) Multi-Purpose Commercial Vehicle Graphics (Full, Partial) Vehicle Decals Fleet Graphics	Smooth Walls / Compound Curves Fleet Panels (Flat with Rivets) Deep Channels / Concave Surfaces Corrugated Panels	30" / 48" 54" / 60"	25 Yards ♦ 50 Yards	Series 3200 / Series 3210 Series 3220 / Series 3270 Series 3310	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Wall Graphics (Interior) Window Graphics Multi-Purpose Commercial Vehicle Graphics (Partial) Vehicle Decals / Fleet Graphics Floor Graphics (Interior) ■	Smooth Walls Glass Common Sign Substrates Soft Curves Fleet Panels (Flat without Rivets) Smooth Floors	30" ▼ 54" / 60"	50 Yards	Series 3170 / Series 3210 Series 3220 / Series 3310 Series 3420	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Wall Graphics (Interior) Vehicle Decals Window Graphics	Painted Smooth Walls Glass	54"	50 Yards	Series 3200 / Series 3210 Series 3220 / Series 3420	Eco-Solvent / Solvent UV / Latex
Indoor Advertising Wall Graphics (Interior) Interior Décor	Common Sign Substrates Smooth Walls	54"	100 Feet	N/A	Eco-Solvent / Solvent UV

♦ 60" only available in 25 Yard length ■ Only when laminated with UL 410 Arlon overlaminate. Please refer to page 23 ▼ Only available in Gloss

WRAPITRIGHT®

INSTRUCTIONAL VIDEO LIBRARY



WATCH THE VIDEO ▶

Wet Application of a Window Graphic

Using a wet application can help make your project picture perfect. This video demonstrates how to correctly install window graphics with a wet application.

For more videos, visit wrapitright.com

PRO  TIPS

SEAM OVERLAPS

The preferred seam overlap is 1/2"-1" when installing interior wall films.

Heavy Duty Digital

Whether your graphics are going cross country, transatlantic or just across town, you will need a film to withstand the extremes.



Wrapped in DPF 9000

	DESCRIPTION	FACE FILM THICKNESS	ADHESIVE	RELEASE LINER	FINISH	APPLICATIONS
ILLUMINITE WRAP®	Fleet Grade * Reflective Film with Low Profile FLITE Technology®	5-Mil (125 Micron)	Permanent (Light Gray)	Lay-Flat Polycoated with Low Profile FLITE Technology®	Gloss	Vehicle Graphics (Full, Partial) Vehicle Decals Fleet Graphics Fleet Markings
DPF 2400XLP	Fleet Grade * Reflective Film with Low Profile X-Scape Technology®	5-Mil (125 Micron)	Permanent (Light Gray)	Lay-Flat Polycoated with Low Profile X-Scape Technology®	Gloss	Vehicle Graphics (Full, Partial) Vehicle Decals Fleet Graphics Fleet Markings
DPF 2400	Fleet Grade * Reflective Film	5-Mil (125 Micron)	Permanent (Clear)	Lay-Flat Polycoated	Gloss	Fleet Markings Fleet Graphics Vehicle Decals Vehicle Graphics (Partial)
DPF 4000	Industrial Grade Calendered Film	3.5-Mil (90 Micron)	Permanent (Clear)	Lay-Flat Polycoated	Satin	Rail & Ocean Container Markings Fleet Markings
DPF 8000™ ULTRA TACK	Industrial Grade Multi-Purpose Calendered Film for Hard-to-Stick Surfaces	3.5-Mil (90 Micron)	Permanent, Ultra Tack (Clear)	Lay-Flat Polycoated	Satin	Wall Graphics (Exterior) ABS Plastic Graphics Floor Graphics (Interior) ♦
DPF 9000	Industrial Grade Heat & Solvent Resistant Calendered Film	3.5-Mil (90 Micron)	Heat, Solvent Resistant Permanent (Clear)	Lay-Flat Polycoated	Satin	Gasoline Pumps Fleet Markings

* Fleet Grade exceeds engineering standards ♦ See PIB for warranty exclusions ▲ 7 year durability applies when paired with an Arlon cast overlaminant



Wrapped in IllumiNITE Wrap® with Series 3220 Overlaminate by Tailored Auto Styling



Wrapped in DPF 4000

RECOMMENDED SURFACES	DURABILITY (UNPRINTED)	ROLL WIDTHS	ROLL LENGTHS	COMPATIBLE OVERLAMINATE	INK COMPATIBILITY
Smooth, Flat Panels / Compound Curves Moderate Channels / Soft Curves Concave Surfaces / Corrugated Panels Fleet Panels (Flat with Rivets)	7 Years	48"	10 Yards 25 Yards 50 Yards	Series 3210 Series 3220 Series 3200	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Smooth, Flat Panels / Compound Curves Moderate Channels / Soft Curves Fleet Panels (Flat with Rivets)	7 Years	48"	10 Yards 25 Yards 50 Yards	Series 3210 Series 3220 Series 3200	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Smooth, Flat Panels / Compound Curves Moderate Channels / Soft Curves Fleet Panels (Flat with Rivets)	7 Years	48"	10 Yards 25 Yards 50 Yards	Series 3210 Series 3220 Series 3200	Eco-Solvent / Solvent
Corrugated Panels Fleet Panels (Flat without Rivets)	7 Years	30" / 49" 54" / 60"	50 Yards	Series 3220 / Series 3420	Eco-Solvent / Solvent UV / Latex
Brick, Concrete & Stucco Textured Surfaces & Substrates Smooth Walls ABS Plastics Smooth Floors ♦	7 Years ♦ ▲	30" / 49" 54" / 60"	50 Yards	Series 3210 / Series 3220 Series 3310 / Series 3420 ProTec Series 3960	Eco-Solvent / Solvent UV / Latex Certified for HP Latex Inks
Corrugated Panels Fleet Panels (Flat without Rivets)	7 Years	30" / 49" 54" / 60"	50 Yards	Series 3220 / Series 3310 Series 3420	Eco-Solvent / Solvent UV / Latex

♦ Only when laminated with UL 410 Arlon overlaminates. Please refer to page 23



WATCH THE VIDEO ▶

Preventing Adhesive Build-Up

Adhesive build-up can collect in a printer when printing film that has a soft and aggressive adhesive system. Learn how to remove adhesive build-up on your wide format printer.

For more videos, visit wrapitright.com



BEFORE YOU Laminate

Always wipe down you media before you laminate. This will ensure that no dust or dirt particles are sealed in.

Flat Out Impressive

Low cost solutions can still turn heads and these films are designed to do just that for your everyday promotional graphics.



Wrapped in DPF 510GTR

	DESCRIPTION	FACE FILM THICKNESS	ADHESIVE	OPACITY	RELEASE LINER	APPLICATIONS
DPF 510GTX/MTX	Promotional Calendered Permanent Film with Low Profile X-Scape Technology®	3.2-Mil (80 Micron)	Permanent (Light Gray)	N/A	Lay-Flat Polycoated with Low Profile X-Scape Technology®	Standard Signage (Permanent) Display Graphics Decals
DPF 510G/M DPF 510GT/MT	Promotional Calendered Permanent Film	3.2-Mil (80 Micron)	DPF 510G/M: Permanent (Clear) DPF 510GT/MT: Permanent (Light Gray)	N/A	Lay-Flat Polycoated	Standard Signage (Permanent) Display Graphics DPF 510GT/MT: Floor Graphics (Interior) *
DPF 510GTR/MTR	Promotional Calendered Removable Film	3.2-Mil (80 Micron)	Removable, Low Tack (Light Gray)	N/A	Lay-Flat Polycoated	Standard Signage (Removable) Display Graphics Window Graphics Floor Graphics (Interior) *
DPF 510GT-HT	Promotional Calendered High Tack Film	3.2-Mil (80 Micron)	Permanent, High Tack (Light Gray)	N/A	Lay-Flat Polycoated	Standard Signage (Permanent) Display Graphics
DPF 50WD WHITE/CLEAR	Removable Window Film	DPF 50WD White: 3.5-Mil (90 Micron) DPF 50WD Clear: 4-Mil (100 Micron)	Removable (Clear)	N/A	Lay-Flat Polycoated	Window Graphics (Interior, Exterior) Glass and Clear Substrates
DPF 208 🌱	Eco Roll-Up Polypropylene	8-Mil (200 Micron)	N/A	80%	N/A	Indoor Advertising Roll-Up Displays Pop-Up Displays
DPF 210 DPF 210PB	Roll-Up Xtreme Polyester	9.8-Mil (250 Micron)	N/A	90%	N/A	Indoor Advertising Roll-Up Displays Pop-Up Displays
DPF 215	Pop-Up Polyester	14.5-Mil (370 Micron)	N/A	90%	N/A	Indoor Advertising Pop-Up Displays

🌱 Environmentally Friendly * Only when laminated with UL 410 Arlon overlaminates. Please refer to page 23 + Only available in 30" width for DPF 510GT



Wrapped DPF 510GTx

RECOMMENDED SURFACES	FINISH	DURABILITY (UNPRINTED)	ROLL WIDTHS	ROLL LENGTHS	COMPATIBLE OVERLAMINATE	INK COMPATIBILITY
Common Sign Substrates	Gloss Matte	3 Years	54" / 60"	50 Yards	Series 3510	Eco-Solvent / Solvent / Latex Certified for HP Latex Inks
Common Sign Substrates DPF 510GT/MT: Smooth Floors	Gloss Matte	3 Years	30" ♦ / 54" / 60"	50 Yards	Series 3510 Series 3420 Series 3220	Eco-Solvent / Solvent / Latex Certified for HP Latex Inks
Common Sign Substrates Glass Smooth Floors	Gloss Matte	3 Years	54" / 60"	50 Yards	Series 3510 Series 3420 Series 3220	Eco-Solvent / Solvent / Latex Certified for HP Latex Inks
Common Sign Substrates	Gloss	3 Years	54" / 60"	50 Yards	Series 3510	Eco-Solvent / Solvent / Latex Certified for HP Latex Inks
Glass High Energy Surfaces	DPF 50WD White: Matte DPF 50WD Clear: Gloss	DPF 50WD White: 2 Years DPF 50WD Clear: 1 Year	54" / 60"	50 Yards	DPF 50WD White: Series 3420 DPF 50WD Clear: Series 3200	Eco-Solvent / Solvent UV / Latex ♦
N/A	Satin	1 Year	36" / 50"	98 Feet	N/A	Eco-Solvent / Solvent
N/A	Satin Pebble	1 Year	36" / 50" / 60" ▲	98 Feet 164 Feet	N/A	Eco-Solvent / Solvent Latex ♦
N/A	Satin	1 Year	36"	98 Feet	N/A	Eco-Solvent / Solvent

▲ Only 60" width available in Satin finish ♦ Not compatible with DPF 50WD Clear ♦ Compatible with Gen 3 Latex Inks



WATCH THE VIDEO ▶

How to Store Vinyl Rolls

By storing your vinyl properly, you'll always get the best performance from your media. This video shows the key elements to storing vinyl in the right environment.

For more videos, visit wrapitright.com



SQUEEGEE BASICS 101

Harder squeegees (made from Teflon) are better at fixing sharper wrinkles, while softer squeegees (made from felt) can help fix wrinkles in curved panels.

Low Cost, High Potential

Make a big picture statement with our range of banner material. Block out the competition but not your creativity. Seeing is believing!



Wrapped in DPF 310BB

	DESCRIPTION	FACE FILM THICKNESS	YARN	OPACITY	FINISH	APPLICATIONS
DPF 313 (500D)	Front-Lit Smooth Promotional Banner	13-oz	500D	97%	Gloss Matte	Indoor & Outdoor Advertising
DPF 313 (1000D)	Front-Lit Smooth Promotional Banner	13-oz	1000D	97%	Gloss Matte	Indoor & Outdoor Advertising
DPF 303	Super Smooth Double-Sided Blockout Banner	13-oz	250D	100%	Satin	Display Graphics
DPF 310BB *	Front-Lit Black Back Lightweight Banner	9-oz	1000D	100%	Matte	Outdoor Advertising
DPF 318	Intermediate Double-Sided Blockout Banner	18-oz	1000D	100%	Gloss Matte ✦	Indoor & Outdoor Advertising Flag Pole Banners

* DPF 310BB is available by custom order ✦ Double-sided printing recommended on Matte ▲ Custom widths and lengths available ✦ Only available in 40 yard length




DPF 313 (500D)

DURABILITY (UNPRINTED)	ROLL WIDTHS ▲	ROLL LENGTHS ▲	INK COMPATIBILITY
1 Year	38" / 54"	40 Yards	Eco-Solvent / Solvent UV / Latex
1 Year	30" ◆ / 38" / 48" ◆ 54" / 63"	40 Yards 50 Yards	Eco-Solvent / Solvent UV / Latex
1 Year	38" / 54" / 62"	50 Yards	Eco-Solvent / Solvent UV / Latex ■
1 Year	126" / 196"	164 Feet	Eco-Solvent / Solvent / UV
1 Year	38" / 54"	50 Yards	Eco-Solvent / Solvent UV / Latex

■ If printing with Latex, print on the side with less of a Matte finish and use Arlon's preset.

Yarn Denier Explained

The strength of a scrim banner is determined by the denier. The denier is the thickness of the thread; the higher the denier, the stronger the banner. 1000 Denier (1000D) banner means that a single thread has been twisted 1000 times to the finished length of an inch (think: string vs rope).



WRAPITRIGHT®

INSTRUCTIONAL VIDEO LIBRARY



WATCH THE VIDEO ▶

Uploading an Arlon Media Profile into Roland Versaworks

Learn step-by-step instructions on how to properly upload Arlon Media Profiles into Roland VersaWorks RIP software.

For more videos, visit wrapitright.com

PRO  TIPS

DOUBLE THE Exposure

Printing on the front and back of block out banner gives your business the distinct advantage—maximum visibility and added durability.



Wrapped in DPF 4600GLX with Series 3220 Gloss

Multiply Your Protection


Shield and protect your everyday signage from the elements. Arlon overlaminates are designed to protect and prolong the life of your graphic.



**Prolonged
Durability**



**Ease of
Application**



**UV
Stability**



**Abrasion
Resistance**



**Quick and
Clean Removal**



Wrapped in DPF 6700 with Series 3220 Overlaminate by Signs Now Broward



Wrapped in DPF 6700 with Series 3220 Overlaminate by Superior Graphics

	DESCRIPTION	FACE FILM THICKNESS	ADHESIVE	RELEASE LINER	FINISH	DURABILITY	ROLL WIDTHS	ROLL LENGTHS
SERIES 3210	Premium Cast Overlaminate	1.3 Mil (35 Micron)	Permanent (Clear)	Clay Coated	Gloss	7 Years	48" / 54" / 60"	25 Yards ▲ 50 Yards
SERIES 3220 *	 Premium Cast Overlaminate	2-Mil (50 Micron)	Permanent (Clear)	Clay Coated	Gloss * Matte Satin Luster	7 Years	30" / 48" 54" / 60"	25 Yards ♦ 50 Yards
SERIES 3270	Premium Cast Overlaminate	2-Mil (50 Micron)	Permanent (Clear)	Clay Coated	Gloss Matte Satin	7 Years	30" / 48" 54" / 60"	50 Yards
SERIES 3310 	Extended Life Polyurethane Overlaminate	1.5-Mil (38 Micron)	Permanent (Clear)	Clay Coated	Gloss	10 Years ♣	54" / 60"	50 Yards
SERIES 3170	Intermediate Cast Overlaminate	1.3-Mil (35 Micron)	Permanent (Clear)	Clay Coated	Gloss	7 Years	54" / 60"	50 Yards
SERIES 3420 *	 Calendered Overlaminate	3-Mil (75 Micron)	Permanent (Clear)	Clay Coated	Gloss * Matte * Satin	5 Years	30" / 48" 54" / 60"	50 Yards
SERIES 3510	Promotional Calendered Overlaminate	3.2-Mil (80 Micron)	Permanent (Clear)	Polycoated Kraft	Gloss Matte	3 Years	54" / 60"	50 Yards

* UL 410 Approved for slip resistance on Series 3220 Gloss and Series 3420 Gloss/Matte  Environmentally Friendly ♣ 10 years vertical exposure and up to 4 years horizontal exposure ▲ Only available in Gloss for 48" width ♦ Only available in Gloss for 48" and 54" width

Clear Solutions

Tough situations require tough solutions. When a standard overlaminate won't do, take your protection up a notch. Protect your graphics from extreme wear and tear while ensuring crystal clear clarity.



Wrapped in DPF 4500GT with Series 3350 Overlaminate



**Extreme
Durability**



**Anti-Graffiti
Protection**



**Temperature
& Chemical
Resistance**



**Abrasion
Resistance**



Clarity



Wrapped in IllumiNITE Wrap® with Series 3200 Overlamine by Graffit Design



Wrapped in DPF 8000™ Ultra Tack with ProTec Series 3960 Overlamine by Fusion Graphics

	DESCRIPTION	FACE FILM THICKNESS	ADHESIVE	RELEASE LINER	FINISH	DURABILITY	ROLL WIDTHS	ROLL LENGTHS
SERIES 3200	Premium High Gloss Optically Clear Overlamine	2-Mil (50 Micron)	Permanent (Clear)	Lay-Flat Synthetic	Gloss	7 Years	30" / 54" / 60"	10 Yards * 100 Feet♣ 50 Yards
SERIES 3350	Anti-Graffiti PVDF Overlamine	2-Mil (50 Micron)	Permanent (Clear)	Lay-Flat Polycoated	Satin	10 Years	49" / 54"	50 Yards
PROTEC SERIES 3960	Heavy Duty Calendered Overlamine	12-Mil (305 Micron)	Permanent (Clear)	Lay-Flat Synthetic	Gloss	2 Years	54"	10 Yards 25 Yards

* Only available in 30" and 54" width ♣ Only available in 54" width