

DreamScape®

Distributed by:

 **Piedmont Plastics®**
where solutions take shape

For more information visit
www.piedmontplastics.com



Bring your design to life with IMPACT & DAZZLE.



TEXTURED WALL MEDIA

specially developed and optically tuned
for digital printing on wide-format solvent,
eco-solvent, UV-Curable and Latex printers



REACH NEW CUSTOMERS! GET INTO THIS FAST GROWING MARKET!



Criss Cross



Canvas



Cabretta



Artist Canvas



Silk



Suede




Mystical




Pueblo



Plaster



Pique



Beads



Sandblast



TEXTURED WALL MEDIA



- High performance strippable commercial grade Type II wallcovering featuring "Easy up, Easy down" system
- Specially designed for high volume digital output
- Available in widths of 54", 60", 75" and lengths of 75', 150', and 300' to fit a wide range of applications
- Exceeds US, Canadian and European Flame and Smoke Requirements. Tested and approved using off the shelf available adhesives
- Meets all CCCW 408D Mildew and Fungal Resistance for wallcovering based on ASTM G21 testing mounting and commercially available adhesives
- Special bulk skid packaging for large volume orders; easier to use, less packaging waste
- Self Extinguishing Technology
- NO ROLL SPLICES!
- Packaging in heavy duty reusable tubes
- Formulated without Lead and Cadmium
- NEW! Now made with LOW VOC vinyl. Tested per CA 1350 air quality standards.
- WA certified NSF 342 Sustainability Standard

FOR MORE INFORMATION CONTACT:

973.625.7923

sales@dreamscapewalls.com

www.dreamscapewalls.com



Restaurant/Ceiling Installation on Luster



Restaurant Chain/Wallcoverings on Suede



Restaurant/Wall & ceiling coverings on Artist Canvas



Office/Wallcovering on Mystical



Retail/Columns, Soffits, & Wallcoverings on Suede

PRODUCT PACKAGING

Each roll is meticulously packaged in a re-usable heavy duty tube

(No flat spots, no creases, no splices)

STD Lengths: 75', 150', 300'

STD Widths: 54", 60", 75" (+/- 1/8")

Core Diameter: 3 inches i.d. Heavy-Duty

*Custom lengths and widths available on request

PHYSICAL PROPERTIES

Product Weight: 20 oz. per lineal yd. (13oz. per sq. yd.)

Vinyl Weight: 17 oz. per lineal yd.

Fabric Weight: 3 oz. per lineal yd.

Thickness: 0.015 to 0.030 in.

*depending on texture

Fabric: Poly-Cotton Osnaburg or

Polyester Nonwoven

*depending on texture

BREAKING STRENGTHS, LBS. FORCE

Machine Direction-warp:

*Exceeds Type II minimum of 50 lbs.

Cross Machine Direction-fill:

*Exceeds Type II minimum of 55 lbs.

TEARING STRENGTH, SCALE

Machine Direction-warp:

*Exceeds Type II minimum of 25lbs.

Cross Machine Direction-fill:

*Exceeds Type II minimum of 25 lbs.

COLD CRACK RESISTANCE @ 20° F

No change

HEAT AGING (7 DAYS @ 158°F)

*Does not become stiff, brittle, discolored, or show loss of grain

SPECIFICATIONS / TESTING / CERTIFICATION

Federal Specification:

*CCC-408-D *Type II *Class A

CFFA Specification:

WA-101 *Type II *Class A

FIRE TESTING

ASTM-E84 Tunnel Test

Class A

NFPA286 Corner Burn Test

Class A

EU Class Flame (EN 15102)

Passed

BS476 Part 6&7

Passed

CAN/ULC-S102.2

Passed

*WA Certified NSF/ANSI 342

*Meets or exceeds requirements for flame spread, smoke developments and flashover.

MOLD/MILDEW/BACTERIAL RESISTANCE

ASTM-G21 Specifications:

Passed all requirements of CCCW-408-D

*Cadmium and Lead Free Formulation