

Sanatec
Sanatec PP
Sanatec
Lite

Physical		Sanatec PP	Sanatec	Lite
Density (g/cm ³)	0.9	0.960 +	0.8	
Absorption	Max.01%	Max 0.01%	Max 0.01%	
Hardness, Shore D	78	69	69	
Mechanical				
Tensile Strength @ Yield (psi)	4,900	4,600	3,200	
Flexural Modulus (psi)	190,000	225,000	228,000	
Notched Izod Impact (fl-lb/in)	0.9	120		
Elongation at Yeild (%)	9	>600	>600	
Thermal				
Vicat Softening Point (°C)	305	129	129	
Heat Deflection Temperature @ 66 psi (°C)	210	82	82	
Coefficient of Linear Thermal Expansion (In./In.°C)	6.5x10 ⁻⁵	6x10 ⁻⁵	6x10 ⁻⁵	
Maximum Service Temperature, Air (°C)	180	180°F	180°F	
Low Temperature Brittleness F ₅₀	-	<-76	<-76	
Melt Index (g/cm ³)	0.5	0.8	0.8	
Flammability Ratings				
Flammability Rating	UL94 HB	UL94 HB	UL94 HB	
Compliances				
Compliances (VO)	FDA, USDA, NSF* (natural only)	FDA, USDA,NSF*	FDA, USDA,NSF*	



Distributed by:


Toll Free: 1.800.277.7898
www.piedmontplastics.com

Physical properties of plastic sheeting are represented as "Typical". Information contained herein is considered accurate to the best of our knowledge. It is offered for your consideration and investigation, and is not to be construed as a representation or warranty expressed or implied. Our warranties are limited to those expressly stated in formal contracts or in conditions of sale on our invoices and order acceptances. Conditions and methods of use may vary and are beyond the control of Vycom; therefore, Vycom disclaims any liability incurred as a result of the use of this product in accordance with the data contained in our physical property charts. No information herein shall be construed as an offer of indemnity for infringement or as a recommendation to use the products in such a manner as to infringe any patent, domestic or foreign.

*Effective Date: January 1st, 2016

The "Typical" properties of our plastic sheet cannot be automatically used when engineering finished components; and the fabricator or end user is responsible for insuring the suitability of our products for their specific application or end use!